

524154

Rec'd PCT/PTO 09 MAR 2005
10/10/05

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025112 A1

(51) International Patent Classification⁷: F02M 53/06, 31/125

(72) Inventor; and

(75) Inventor/Applicant (for US only): RIGNEY, Shaun, Thomas [AU/AU]; 9 Currajong Street, Doncaster East, Victoria 3109 (AU).

(21) International Application Number:
PCT/AU2003/001156

(74) Agent: GRIFFITH HACK; 509 St Kilda Road, Melbourne, Victoria 3004 (AU).

(22) International Filing Date:
5 September 2003 (05.09.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
2002951332 11 September 2002 (11.09.2002) AU
2003904065 1 August 2003 (01.08.2003) AU

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

(71) Applicant (for all designated States except US): VAPO-RATE PTY LTD [AU/AU]; Level 10, 257 Collins Street, Melbourne, Victoria 3000 (AU).

[Continued on next page]

(54) Title: FUEL DELIVERY SYSTEM



(57) Abstract: A fuel delivery system for an IC engine includes an injector (240) which is heated as its region to elevate the temperature of the fuel in the end region and so that when the fuel is ejected from the end region, it immediately converts to vapour. Heating of the end region is performed either by direct conduction from the engine or by an electrical heating element. A gasket (22) of heat conducting material is provided between the cylinder head and the inlet manifold (200) so heat is conducted to the inlet manifold (200) and then to injector (240). An electrical heating element (320, 380) is provided surrounding the end region of the injector so that it can heat up the end region immediately without having to wait for the engine to reach operating temperature.

BEST AVAILABLE COPY

WO 2004/025112 A1